

356mm HEAVY DUTY ELECTRONIC OPEN END PUNCH

FEATURES (See Specifications on Back)

New LED Diagnostic Display.

Patented Anti-Jam Feature Detects Punch Overload. Triggers Auto Reversing Function to Eliminate Punch Jams. Also features Manual Reversing as a Backup.

Rated up to 55 Sheets or 110 Pages of 80gsm bond. The Number of Sheets Depends on the Paper Weight and Punch Pattern Used. (15,000 to 18,000 SPH). 90 Cycles Per Minute.

Punch up to 10 Plastic Mylar Sheets Regardless of Hole Pattern (depending on Mylar Mil thickness).

Patented "QCDS", Quick Change Die System.
No Tools, Nothing to Take Apart. All Punch Pins
Easily Disengage.

The HD 7700 Has more than 20 Interchangeable Dies Available with 12 Standard Hole Patterns.

Comes With Your Choice of one Standard Die. (Ask for Details)

356mm Open Ended Punching, Allows for Wider Applications.

New Paper Entry Chute for easy paper insertion.

Extra High Capacity Waste Chip Tray with New View Access. No Sensors Needed.

Smooth, Quiet, Power on Demand Operation.

"Accu-Set" paper adjustment knob for fine adjustments on odd paper sizes.

Use Foot Pedal, Versa Switch, or Palm Activation Switch

Extremely Durable All Metal Construction.

OPTIONAL FEATURES

Can be ordered with the Versa Switch or the New Palm Switch (shown here).





THE ULTIMATE IN:

Quality Paper Punching and Book Binding Equipment at Affordable Prices

www.RHIN-O-TUFF.com

MACHINE SPECIFICATIONS FIECTRICAL WEIGHT **DIMENSIONS** REQUIREMENTS VOLTS AC **AMPS** MACHINE SHIPPING **HEIGHT** WIDTH **DEPTH** Hz 230 50 36.4 Kg 547 mm 2 38.6 Kg 216 mm 534 mm 80 lbs. 85 lbs. 8 1/2" 115 4 60 21" 22 1/2" 12 Standard Punch Die Patterns Available. All Other Patterns Available Upon Request.









the HD 7700 356mm

OPEN END PUNCH

THE HD 4270





wire closer modules



























