# innovate...laminate

## The Easymount<sup>™</sup> double hot roller system gives you total flexibility to mount, laminate and encapsulate.



## Design

With advanced features and a new design, the Easymount<sup>™</sup> is capable of delivering premium quality results for graphics and signage material.

## Performance

There are 2 models to choose from in the range, the 1180 or 1650, both of which can competently produce a highly efficient 3.9 metres per minute.

## Enhancements

Many features have been enhanced on the models including additional mandrel holders for storing spare rolls and a larger feed table for easy material loading.

#### **IDEALLY SUITED FOR**

- · cold laminates (pressure sensitive)
- encapsulating film
- mounting prints to boards
- applying vinyls
- application tapes
- · applying adhesive films

and many more ...

#### **GREAT FOR USE IN**

- commercial printers
- copy and print shops
- · exhibition graphics
- reprographics bureau
- sign makers





# EASYMOUNT<sup>™</sup> DH

## EM-1180DH / EM-1650DH

#### **FEATURES**

- · hot & cold mounting, laminating and encapsulating
- solid construction heavy duty system
- independently heated top or bottom roller
- take up mandrel for release liner paper
- variable speed control
- large rollers for even pressure
- handy reverse mechanism
- low maintenance
- foot pedal for added control





| specifications                  | EM-1180 DH                             | EM-1650DH         |  |
|---------------------------------|--|-------------------|--|
| approx laminating speed (m/min) | 3.9                                    | 3.9               |  |
| maximum width (mm)              | 1180                                   | 1650              |  |
| mounting thickness (mm)         | 25                                     | 25                |  |
| roller diameter (mm)            | 110                                    | 131               |  |
| warm-up time (mins)             | 10                                     | 20                |  |
| hot roller heater system        | internal infrared                      | internal infrared |  |
| laminating temperature (°C)     | 0-140                                  | 0-130             |  |
| speed/temp control              | dial keypad                            | dial keypad       |  |
| pressure adjustment             | manual                                 | manual            |  |
| film core (mm)                  | 75                                     | 75                |  |
| power supply AC (V–Hz)          | 220/240–50-60 (30 amp supply required) | 415V / 3Ø         |  |
| power consumption (W)           | 3950                                   | 5150              |  |
| dimensions (mm)                 | 1680x595x1220                          | 2170x785x1265     |  |
| gross machine weight (kg)       | 270                                    | 366               |  |
| gross stand weight (kg)         | 92                                     | 108               |  |
| warranty (year)                 | 1                                      | 1                 |  |



Vivid Laminating Technologies Ltd

# Call +44 (0) 845 1 30 40 50

St. Georges House, Whitwick Road, Coalville, Leicestershire, LE67 3FA, United Kingdom WEB www.vivid-online.com EMAIL sales@vivid-online.com FAX +44 (0) 845 1 30 70 80