Xtratus Flex®



Model Xtratus Flex® is both a design and technical revolution within security fog. Its elegant, discreet and patented design compliments the newest technology on the inside with patented fluid system technology. The fluid discharge almost feels like a minor explosion. Xtratus Flex® is widely used in private homes and exclusive offices and shops.

Features:

- Discharges 250 m^3 of security fog in just 16 seconds!*
- Flexible adjustment of the performance:
  Pick between 2, 3 or 4 fog discharges pr. fluid container**
- Compatible with any alarm system
- 100% silent in standby mode
- Patented design for installation in corners
- The unit works also without the installed backup battery

**It's important to perform a test firing of the installation - and not only rely on the calculation of cubic metres.*

***Only if programmed to 3 or 4 discharges the Xtratus Flex® counts the used discharges. After the last possible discharge the fluid container has to be changed and the Fog Cannon™ will have to be reset by an authorised alarm installer.*

Specifications:


Performance/fog volume pr. fluid container:* - 16 sec. (2 discharges) - 11 sec. (3 discharges) - 7 sec. (4 discharges)
Prepared for 0,4 l. fluid container (not included)
Enough fluid for up to 4 discharges in one fluid container
Power consumption: 1000 W
Mains connection: 230V, 50 Hz
Standby consumption after heating up: 60 W (on average)
Standby consumption when heat is disabled: 5-10 W
Heating time from cold: 8 min
Re-heating time after fog discharge: 0-5 min
Operating temperature (min./max.): 5/80°C
Input: 3 signals (arming, trig 1, trig 2)
Output: 2 signals
Output power for verification sensor (PIR), 9V DC
On/off dipswitches for setting of signals and heating
Backup of electronics (9V Alcaline)
Power backup after power failure: 17 min
Optical, audible and electrical signals/indicators
Internal and external status indicator
Anti-sabotage, impact-resistant steel casing
Colours available: White
Dimensions: L: 650, W: 140, H: 148 mm
Installation weight: 10 kg

Printing errors excepted. Subject to changes to technical data.



2 year warranty

European quality - Danish design. Xtratus Flex® comes with a 2 year warranty.



3-hole straight nozzle

Xtratus Flex® comes with a 3-hole nozzle. The Xtratus Flex® nozzle cannot be exchanged.



Xtratus Flex® fog fluid

Sturdy fluid can with fog fluid: Extra white and dry fog with extended dissipation time. Quick and easy replacement without fog fluid spillage.

PROTECT® | SECURED IN SECONDS

PROTECT A/S · Hasselager Centervej 5 · DK-8260 Viby J · Tel.: (+45) 86 72 18 81 · Fax: (+45) 86 72 18 82 · Mail: info@protectglobal.com